



Candidate: \_\_\_\_\_

Successful

Evaluator: \_\_\_\_\_

Unsuccessful

Date: \_\_\_\_\_

**1006-SKILL-32**

<b>Standard:</b>	NFPA 1006, 6.1.8 2013 edition
<b>Task:</b>	Descend a fixed rope in a high-angle environment
<b>Performance Outcome:</b>	The person descending is attached to the fixed rope in a manner that will not allow him or her to fall; the person descending is attached to the rope by means of a descent control device; the speed of descent is controlled; injury to the person descending is minimized; the person descending can stop at any point on the fixed rope and rest suspended by his or her harness; the system will not be stressed to the point of failure; the system is suitable for the site; and the objective is reached.
<b>Conditions:</b>	Given an anchored fixed-rope system, a specified minimum travel distance for the rescuer, a system to allow descent of a fixed rope, a belay system, a life safety harness worn by the person descending, and personal protective equipment.
<b>Candidate Directive:</b>	“Descend the fixed rope in a high-angle environment”

NO.	TASK STEPS	TEST	
		Successful	Unsuccessful
1	A fixed rope was descended in a high-angle environment		
2	The person descending was attached to the fixed rope in a manner that did not allow him or her to fall		
3	The person descending was attached to the rope by means of a descent control device		
4	The speed of descent was controlled		
5	Injury to the person descending was minimized		
6	The person descending could stop at any point on the fixed rope and rest suspended by his or her harness		



7	The system was not stressed to the point of failure		
8	The system was suitable for the site		
9	The objective was reached		

**Evaluator/Candidate Comments:**

---

---

---

---

---

\_\_\_\_\_  
**Candidate** (print and sign)

\_\_\_\_\_  
**Date**

\_\_\_\_\_  
**Evaluator** (print and sign)

\_\_\_\_\_  
**Date**